



ABATRON, INC.

5501 – 95th Ave., Kenosha, WI 53144 U.S.A
(262) 653-2000 Fax (262) 653-2019
www.abatron.com e-mail: info@abatron.com
24 Hour Emergency No: (800) 424-9300

Material Safety Data Sheet

SECTION 1: PRODUCT IDENTIFICATION

PRODUCT NAME: ABOCRETE B (ABOCURE 8309-1)
PRODUCT CODE: 8309-1B
CLASS: LIQUID EPOXY COREACTANT

DATE PREPARED: 05/20/2002
PRODUCT DESCRIPTION:
EPOXIDE RESIN COMPOUND

SECTION 2: HAZARDOUS INGREDIENTS

TRADE SECRET: PROPRIETARY FORMULATED AMINES

SECTION 3: PHYSICAL DATA

COLOR: CLEAR, STRAW COLOR
PHYSICAL STATE: LIQUID
MELTING POINT: NA
SOLUBILITY IN WATER: MODERATE
% VOLATILE BY VOL: 0

ODOR: LIGHT AMMONIA
SPECIFIC GRAVITY: 0.95 – 0.97
BOILING POINT: >121°C (>250°F)
VAPOR DENSITY (AIR=1): NA

SECTION 4: FIRE AND EXPLOSION DATA

FLASH POINT: >250°F
LEL: N/A

AUTOIGNITION TEMP. : N/A
UEL: N/A

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, AND SAND OR LIMESTONE FOR SMALL FIRE.

SPECIAL FIRE FIGHTING PROCEDURES: A FACE SHIELD SHOULD BE WORN. FIREFIGHTERS SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES, BODY SUIT AND SELF-CONTAINED BREATHING APPARATUS.

SPECIAL FIRE FIGHTING EQUIPMENT: NONE

SECTION 5: HEALTH HAZARDS

INGESTION: LOW SINGLE ORAL TOXICITY: LD50(RAT): >16G/KG.
EYE CONTACT: EXTREME IRRITATION
SKIN CONTACT: ONLY MINOR IRRITATION. PRIMARY IRRITATION TEST SCORE 1.2.
SKIN ABSORPTION: PROLONGED OR REPEATED CONTACT MAY CAUSE INJURY.
INHALATION: NOT LIKELY A PROBLEM AT ROOM TEMPERATURE. VAPORS FROM HEATED MATERIAL MAY BE IRRITATING.
EFFECT OF OVEREXPOSURE: MAY CAUSE SKIN SENSITIZATION. NONE OTHER KNOWN.

SECTION 6: FIRST AID

EYE CONTACT: IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. REFER TO MEDICAL PERSONNEL.
SKIN CONTACT: IMMEDIATELY FLUSH AFFECTED AREA WITH WATER FOR AT LEAST 15 MINUTES. CONTACT WILL PROBABLY CAUSE NO MORE THAN IRRITATION.
INHALATION: REMOVE TO FRESH AIR. CONSULT MEDICAL PERSONNEL.
INGESTION: TOXIC. INDUCE VOMITING IF LARGE AMOUNTS ARE INGESTED.

SECTION 7: STABILITY AND REACTIVITY

STABILITY: STABLE UNDER NORMAL CONDITIONS. PROLONGED EXCESSIVE HEAT MAY CAUSE PARTIAL DEGRADATION.

INCOMPATIBILITY: EPOXY RESINS UNDER UNCONTROLLED CONDITIONS.

HAZARDOUS POLYMERIZATIONS: NONE

HAZARDOUS DECOMPOSITION PRODUCTS: NONE UNDER NORMAL CONDITIONS.

SECTION 8: ACCIDENTAL RELEASE MEASURES

ACTION TO TAKE FOR SPILLS (USE APPROPRIATE SAFETY EQUIPMENT): SOAK IN ABSORBENT MATERIAL OR SCRAPE UP. SCRUB WITH 5% ACETIC ACID TO EMULSIFY. RINSE WITH VERY HOT WATER.

DISPOSAL METHOD: BURY IN APPROPRIATE LANDFILL. (OPTIONAL) BURN COMBUSTIBLE PORTION IN ADEQUATE INCINERATOR.

SECTION 9: HANDLING AND STORAGE

VENTILATION: SUFFICIENT TO MINIMIZE VAPOR EXPOSURE IF GENERATED.

RESPIRATORY PROTECTION: NONE LIKELY NEEDED.

PROTECTIVE CLOTHING: CLEAN, BODY-COVERING CLOTHING. DISPOSABLE PLASTIC OR RUBBER GLOVES. DISPOSAL CONTAINERS AND PAPER IN WORK AREA.

EYE PROTECTION: SAFETY GLASSES.

SECTION 10: PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: NONE EXCEPT NORMAL HANDLING CARE. PRACTICE GOOD CAUTION AND PERSONAL CLEANLINESS TO AVOID EYE AND SKIN CONTACT. AVOID BREATHING VAPORS IF GENERATED.

SECTION 11: TRANSPORT INFORMATION

DOT (USA) STATUS: NOT REGULATED

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED, IS MADE.