



Safety Data Sheet

Issue Date: 24-Jan-2022

Revision Date: 16-May-2022

Version 2

1. IDENTIFICATION

Product identifier

Product Name Multi-purpose Pig Putty

Other means of identification

SDS # MSD-001

Recommended use of the chemical and restrictions on use

Recommended Use Emergency patches and repairs of a wide variety of materials.

Uses Advised Against Not for structural repairs.

Details of the supplier of the safety data sheet

Supplier Address

New Pig Corporations
One Pork Avenue
Tipton, PA 16684-0304
Information: 1-800-468-4647
Email: hothogs@newpig.com
Website: www.newpig.com

Emergency telephone number

Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Putty, gray color after cure

Physical state Solid

Odor Pungent Sulfurous

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A

Signal Word

Danger



Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace
Wear protective gloves

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of water and soap
Take off contaminated clothing and wash before reuse
If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Talc, without asbestiform fibers	14807-96-6	20-50
Mercaptan terminated polymer	72244-98-5	10-20
Glass Beads	65997-17-3	10-20
bisphenol A epoxy resin	25068-38-6	5-10
Bisphenol A diglycidyl ether	1675-54-3	5-10
Zinc sulfide	1314-98-3	1-5
2,4,6-tri(dimethylaminomethyl)phenol	90-72-2	<2
Silica, Quartz	14808-60-7	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures**

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if irritation occurs.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Get medical attention if symptoms occur.

Most important symptoms and effects, both acute and delayed

Symptoms Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Hazardous combustion products Carbon dioxide (CO₂). Carbon monoxide. Nitrogen oxides (NO_x). Sulfur oxides. Halogenated compounds. Metal oxides.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Collect contaminated fire extinguishing water separately. Do not allow it to enter drains or surface water.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required. Avoid dust formation in cured mode when sanding, drilling or abrading.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further spillage of solid product if safe to do so.

Methods for Clean-Up Collect dust or particulates using a vacuum cleaner with a HEPA filter. Place in appropriate containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Shelf Life: ~2 years (in original tube with cap on).

Incompatible Materials

Oxidizing agents. Acids. Bases. Amines. (For compatibility guide, go to www.NewPig.com or call 1-800-468-4647).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Glass Beads 65997-17-3	TWA: 1 fiber/cm ³ respirable fibers: length >5 μm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m ³ inhalable particulate matter	-	-
Silica, Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 μg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Appropriate engineering controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits. Showers. Eyewash stations.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Wear safety glasses with side shields (or goggles). Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection

Use impervious gloves. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection

None required unless sanding or abrading. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state
Appearance
Color

Solid
Putty, gray color after cure
Gray color after cure

Odor
Odor Threshold

Pungent Sulfurous
Not determined

Property

Values

Remarks • Method

pH
Melting point / freezing point
Boiling point / boiling range

Not determined
Not determined
Not determined

Flash point	Not determined
Evaporation Rate	Not determined
Flammability (Solid, Gas)	Not determined
Flammability Limit in Air	
Upper flammability or explosive limits	Not determined
Lower flammability or explosive limits	Not determined
Vapor Pressure	Not determined
Vapor Density	Not determined
Relative Density	1.95
Water Solubility	Not determined
Solubility in other solvents	Not determined
Partition Coefficient	Not determined
Autoignition temperature	Not determined
Decomposition temperature	Not determined
Kinematic viscosity	Not determined
Dynamic Viscosity	Not determined
Explosive Properties	Not determined
Oxidizing Properties	Not determined

Other information

VOC Content	0%
Bulk density	Work life at 75°F (24°C): 3-5 minutes Functional cure (lap shear tensile strength=200 psi): 60 minutes Cure time to full cure at 70°F (21°C): 24 hours

10. STABILITY AND REACTIVITY**Reactivity**

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures >35°C (95°).

Incompatible materials

Oxidizing agents. Acids. Bases. Amines. (For compatibility guide, go to www.NewPig.com or call 1-800-468-4647).

Hazardous decomposition products

Carbon dioxide (CO₂). Carbon monoxide. Nitrogen oxides (NO_x). Sulfur oxides. Halogenated compounds. Metal oxides.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

Eye Contact	Avoid contact with eyes.
Skin Contact	Avoid contact with skin.
Inhalation	Do not inhale.

Ingestion Do not ingest.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol A diglycidyl ether 1675-54-3	= 11300 µL/kg (Rat)	= 20000 mg/kg (Rabbit)	-
bisphenol A epoxy resin 25068-38-6	= 11400 mg/kg (Rat)	-	-
Zinc sulfide 1314-98-3	> 2 g/kg (Rat)	> 2 g/kg (Rat)	> 5040 mg/m ³ (Rat) 4 h
2,4,6- tri(dimethylaminomethyl)phenol 90-72-2	= 1200 mg/kg (Rat)	= 1280 mg/kg (Rat)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested. Silica (quartz) is a possible carcinogen when it appears as a respirable dust. (In cured mode when sanded, drilled or abraded).

Chemical name	ACGIH	IARC	NTP	OSHA
Bisphenol A diglycidyl ether 1675-54-3		Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

STOT - repeated exposure Respirable crystalline silica causes damage to organs (lung effects, immune system effects, and kidney effects) through prolonged or repeated exposure.

Numerical measures of toxicity

Not determined.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Talc 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods**Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Zinc sulfide 1314-98-3	Toxic

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

Not regulated

IATA

Not regulated

IMDG

Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Talc	X	ACTIVE	X	X	X	X	X	X	X
Glass Beads	X	ACTIVE	X	X	X	X	X	X	X
Mercaptan terminated polymer	X	ACTIVE	X			X	X	X	X
Bisphenol A diglycidyl ether	X	ACTIVE	X	X	X	X	X	X	X
bisphenol A epoxy resin	X	ACTIVE	X	X	X	X	X	X	X
Zinc sulfide	X	ACTIVE	X	X	X	X	X	X	X
2,4,6-tri(dimethylaminomethyl)phenol	X	ACTIVE	X	X	X	X	X	X	X
Silica, Quartz	X	ACTIVE	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

*KECL - Korean Existing and Evaluated Chemical Substances**PICCS - Philippines Inventory of Chemicals and Chemical Substances**AICS - Australian Inventory of Chemical Substances***US Federal Regulations****CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Zinc sulfide - 1314-98-3	1314-98-3	1-5	1.0

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc sulfide		X		

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Silica, Quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Talc 14807-96-6	X	X	X
Zinc sulfide 1314-98-3	X		X
Silica, Quartz 14808-60-7	X	X	X

16. OTHER INFORMATION**NFPA****Health Hazards**

Not determined

Flammability

Not determined

Instability

Not determined

Special Hazards

Not determined

HMIS**Health Hazards**

Not determined

Flammability

Not determined

Physical hazards

Not determined

Personal Protection

Not determined

Issue Date:

24-Jan-2022

Revision Date:

16-May-2022

Revision Note:

SDS sections updated 3

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet