



MATERIAL SAFETY DATA SHEET

PIG® Drive-Over DRAINBLOCKER® Drain Cover (MSD-178)

Page 1 of 2

1. Product And Company Identification

Product Identifier: PIG® Drive-Over DRAINBLOCKER® Drain Cover

General Use: PIG® Drive-Over DRAINBLOCKER® Drain Cover is designed to block liquids from getting into drain systems with a unique patented weather, abrasion and puncture-resistant Rubber topped /Polyurethane DRAINBLOCKER® bottom. This composite can withstand being driven over and can be used in heavy traffic areas, prolonged indoor or outdoor operations as well as emergency response situations.

Product Description: Composite Black Rubber top and a Polyurethane Blue Bottom in a round, square and rectangular shape.

COMPANY PROFILE: **EMERGENCY TELEPHONE:**

New Pig Corporation
One Pork Avenue
Tipton, PA 16684-0304
Information Number
1-800-468-4647

INFOTRAC
200 North Palmetto Street
Leesburg, FL 34748
24 hrs, 7 days/week
1-800-535-5053

Website: www.newpig.com, **Email:** hothogs@newpig.com

2. Hazards Identification

POTENTIAL HEALTH EFFECTS:

Eye Contact: No hazard in normal use of product

Ingestion: No toxic effects are expected.

Inhalation: No hazard in normal use of product

Skin Contact: No hazard in normal use of product

Chronic: Not established

3. Composition/Information on Ingredients

<u>Components</u>	<u>wt. %</u>	<u>CAS Registry #</u>
<u>Top layer</u>		
Rubber	100	Mixture
<u>Bottom layer</u>		
Polyurethane elastomer	100	68400-67-9

4. First Aid Measures

Eye Contact: Not applicable

Ingestion: Not applicable

Inhalation: Not applicable

Skin Contact: Not applicable

5. Fire Fighting Measures

Flash Point: Not established **Method:** Not applicable

Auto-ignition Temperature: Not established

Flammable Limits: Not established

Conditions of Flammability: Not established

Explosive Properties: Not applicable

Extinguishing Media: Water, chemical foam, dry chemical or carbon dioxide.

5. Fire Fighting Measures (Continued)

Special Fire Fighting Procedures: Firefighters should use self contained breathing apparatus. Avoid breathing smoke, fumes, and decomposition products. Use water spray to drench smoldering elastomer. Product may melt after ignition to form flammable liquids.

Hazardous Combustion Products: Carbon monoxide, oxides of nitrogen and hydrogen cyanide.

Unusual Hazards: Burning produces intense heat, dense smoke, and toxic gases such as carbon monoxide, carbon dioxide, oxides of nitrogen, sulfur dioxide and traces of hydrogen cyanide.

6. Accidental Release Measures

Spill or Leak Procedures: Pick up and handle as any other inert solid material.

7. Handling and Storage

Handling and Storage Precautions: The PIG® Drive-Over DRAINBLOCKER® Drain Cover should be stored flat in the original container, wrapped in the original plastic film or equivalent.

Storage Temperature: When not in use, should be stored in a cool / dry sheltered compartment (i.e.: out of sunlight)

Storage Pressure: Not applicable

Shelf Life: Approximately 5 years.

General: After use, decontaminate PIG® Drive-Over DRAINBLOCKER® Drain Cover. During use or storage, product has been found to occasionally connect itself together. Do not let product touch itself. **NOTE: Bottom layer:** Due to the nature of softer urethane, the physical properties of this product may change over time with exposure to certain environmental conditions, like temperature, humidity and UV radiation. Please inspect the stored product regularly to ensure it is in a usable state. The container can be hazardous when empty. Follow label cautions even after the container is empty. Do not re-use empty containers for food, clothing or products for human or animal consumption, or where skin contact can occur.

8. Exposure Controls/Personal Protection

Engineering Controls: None required

PERSONAL PROTECTION

Eyes: None required

Respirator: None required

Gloves: None required

Other: Do not cut PIG® Drive-Over DRAINBLOCKER® Drain Cover with hot wire or hot branding unless local exhaust is sufficient to maintain isocyanate fumes below the TLV for TDI (0.005 ppm TWA / 0.02 ppm STEL) or MDI (0.005 ppm TWA). In addition, an air purifying respirator with an organic cartridge is required.

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):

EXPOSURE LIMITS 8 hrs. TWA (ppm)

OSHA PEL ACGIH TLV

None



MATERIAL SAFETY DATA SHEET

PIG® Drive-Over DRAINBLOCKER® Drain Cover (MSD-178)

Page 2 of 2

9. Physical and Chemical Properties

Appearance: Black rubber top with a blue polyurethane bottom
Physical State: Solid
Odor: Slight or no odor **Odor Threshold:** Not applicable
Vapor Pressure: Not applicable **Vapor Density:** Not applicable
Specific Gravity: Bottom layer: 1.05 - 1.26
Solubility in Water: Insoluble
Coefficient of Water/Oil Distribution: Not available
pH: Not applicable
Boiling Point: Not applicable
Evaporation Rate: Not applicable
Melting Point: Bottom layer: 380° F (193° C). Will degrade above 280° F (138° C).

10. Stability and Reactivity

General: This is a stable material.
Conditions of Reactivity: Not established
Incompatible Materials: May be affected by strong acids and bases
Conditions to Avoid: Hot wire and hot branding. High temperatures and prolonged exposure to humid conditions have been known to cause degradation of Blocker material.
Hazardous Decomposition: Decomposition through burning produces fumes consisting of organic particulate, gaseous hydrocarbons, carbon dioxide, carbon monoxide, and may contain traces of Toluene Diisocyanate or Diphenylmethane Diisocyanate, Hydrogen cyanide, Acrolein and oxides of nitrogen.
Hazardous Polymerization: Will not occur

11. Toxicological Information

LD50: Not available
LC50: Not available
Carcinogenicity: IARC: Not established
National Toxicology Program: Not established
OSHA: Not established
California Prop 65: No listed ingredient
Reproduction Toxicity: Not available
Teratogenicity: Not available
Mutagenicity: Not available
Synergistic Products: Not available
Irritancy of Product: See Section 3.
Sensitization to Product: Not available

12. Ecological Information

No data available

13. Disposal Considerations

Waste Disposal Method: If unused, not considered a hazardous material. Dispose of material according to federal, state, and local laws.

14. Transport Information

DOT (Department of Transportation):
Proper Shipping Name: Not regulated
Hazard Class: Not regulated
Identification Number: Not applicable

15. Regulatory Information

CERCLA (Comprehensive Environmental Response Compensation and Liability Act): No Reportable Quantity
OSHA Hazard Communication Standard, 29 CFR 1910.1200: No listed ingredient
SARA Title III (Superfund Amendments and Reauthorization Act): No listed ingredient
TSCA (Toxic Substances Control Act): All ingredients are listed.

16. Other Information

NFPA Hazard Ratings: **Health - 0**
none → extreme **Fire - 1**
0 → 4 **Reactivity - 0**

Reason for Issue: Reviewed, added or moved information in Sections 1, 2, 3, 8 and 16 in preparation for the new GHS format.
Prepared by: Dale Gatehouse, Entreprises Krenda Inc.
Approved by: Lisa Baxter, New Pig Corporation
Previous Date of Issue: 10/07/2008
Revised Date: 02/25/2010
MSDS Number: MSD-178

The following is in lieu of all warranties, expressed or implied: All information provided is based on testing and data believed to be accurate. PIG® is a registered trademark of New Pig Corporation. All New Pig Corporation trademarks are protected by U.S. and International law.

Approval Date: 02/25/2010