

## 30-Gallon Open-Head UN Rated Steel Drum

DRM1336 30 gal., UN1A2/X235/S,  
UN1A2/Y1.5/150, 1.2/1.2/1.2 mm Thick

Tough, UN Rated open top drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated for shipping of either liquids or solids and tested to help ensure safe shipping of hazardous materials
- Open-head design and removable lid offer full, convenient access to inside of drum
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 12-gauge bolt ring closure, sponge rubber gasket and plated bolt/nut provide tight seal to help prevent leaks and spills
- Steel lid and body and bottom meet strict wall thickness requirements to ensure strength, durability and long life



Item#	Description	Dimensions	Weight
DRM1336-ULD	Unlined	ext. dia. 18.8" x 29" H	33 lbs.
DRM1336-LD	Lined	ext. dia. 18.8" x 29" H	33 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM1336-ULD	Unlined	ext. dia. 47.8cm x 73.7cm H	15 kg
DRM1336-LD	Lined	ext. dia. 47.8cm x 73.7cm H	15 kg

### Specifications

Drum Lid Closure	Open-Head
Lining	Lined; Unlined
Thickness	1.2/1.2/1.2 mm Thick
Color	Black
Dimensions	ext. dia. 18.8" x 29" H
Storage Capacity	30 gal.
Bung Type	No Bung Holes
Drum Type	Steel Drum
Interior Dimensions	18.25" Dia. x 26.7" H
Lid Type	Nut & Bolt Ring
Sold as	1 each

<b>Weight</b>	33 lbs.
<b>Composition</b>	Drum - Carbon Steel Bung Gasket - EPDM Lining - Phenolic Epoxy
<b>UNSPSC</b>	24112108
<b>Pigalog® Page Number</b>	<a href="#">Page 308</a>

## Metric Equivalent

<b>Dimensions</b>	ext. dia. 47.8cm x 73.7cm H
<b>Storage Capacity</b>	113.6 L
<b>Weight</b>	15 kg

## Technical Information

### Certifications, Approvals and Ratings

UN1A2/X235/S,UN1A2/Y1.5/150

#### USOnly

This product can ONLY be shipped to the United States.

### Certifications, Approvals and Ratings

UN1A2/X235/S,UN1A2/Y1.5/150

#### USOnly

This product can ONLY be shipped to the United States.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)