

30-Gallon Tight-Head UN Rated Steel Drum

DRM1426 30 gal., UN1A1/X1.8/300, 1.5/0.9/1.5 mm Thick

Tough, UN Rated drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated for Packing Groups I, II and II and tested to help ensure safe shipping of hazardous materials
- Tight-head design is equipped with 2" NPT and 3/4" NPT bungs
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- Steel top, bottom and body meet strict wall thickness requirements to ensure strength, durability and long life



Item#	Description	Dimensions	Weight
DRM1426-ULD	Unlined	ext. dia. 19.25" x 29.5" H	21 lbs.
DRM1426-LD	Lined	ext. dia. 19.25" x 29.5" H	21 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM1426-ULD	Unlined	ext. dia. 48.9cm x 74.9cm H	9.5 kg
DRM1426-LD	Lined	ext. dia. 48.9cm x 74.9cm H	9.5 kg

Specifications

Drum Lid Closure	Tight-Head
Lining	Lined; Unlined
Size	30 gal.
Thickness	1.5/0.9/1.5 mm Thick
Color	Black
Dimensions	ext. dia. 19.25" x 29.5" H
Storage Capacity	30 gal.
Bung Type	2" NPT and .75" NPT (Tri-Sure) Bungs
Drum Type	Steel Drum
Interior Dimensions	18.75" Dia. x 29" H
Lid Type	Tight-Head
Sold as	1 each
Weight	21 lbs.

Composition

Drum - Steel
Lining - Phenolic Epoxy
Gasket - Buna-N

UNSPSC

24112108

Pigalog® Page Number

Page 313

Metric Equivalent

Dimensions

ext. dia. 48.9cm x 74.9cm H

Storage Capacity

113.6 L

Weight

9.5 kg

Technical Information

Certifications, Approvals and Ratings

UN1A1/X1.8/300

USOnly

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

UN1A1/X1.8/300

USOnly

This product can ONLY be shipped to the United States.



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com