

## 30-Gallon Tight-Head UN Rated Steel Drum

DRM845 30 gal., UN1A1/Y1.5/300, 0.9/0.9/0.9 mm

Tough, UN Rated drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Tight-head design is equipped with 2" NPT and 3/4" NPT bungs
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 20-gauge steel top, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life



Item#	Description	Dimensions	Weight
DRM845-ULD	Unlined	ext. dia. 19.25" x 29.5" H	26 lbs.
DRM845-LD	Lined	ext. dia. 19.25" x 29.5" H	26 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM845-ULD	Unlined	ext. dia. 48.9cm x 74.9cm H	11.8 kg
DRM845-LD	Lined	ext. dia. 48.9cm x 74.9cm H	11.8 kg

### Specifications

Lining	Lined; Unlined
Thickness	0.9/0.9/0.9 mm
Color	Black/White
Dimensions	ext. dia. 19.25" x 29.5" H
Storage Capacity	30 gal.
Bung Type	2" NPT and .75" NPT (Tri-Sure) Bungs
Drum Type	Steel Drum
Interior Dimensions	18.75" Dia. x 29" H
Lid Type	Tight-Head
Sold as	1 each
Weight	26 lbs.
# per Pallet	8
Composition	Drum - Steel Bung Gasket - Buna-N

## Metric Equivalent

**Dimensions**

ext. dia. 48.9cm x 74.9cm H

**Storage Capacity**

113.6 L

**Weight**

11.8 kg

## Technical Information

**Certifications, Approvals and Ratings**

UN1A1/Y1.5/300

**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)