

5-Gallon Tight-Head UN Rated Steel Drum with Handle

DRM687 5 gal., UN1A1/X1.6/250, 0.9/0.9/0.9 mm Thick

Tough, UN Rated drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Tight-head design is equipped with 2" NPT and 3/4" NPT bungs
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance



Item#	Description	Dimensions	Weight
DRM687-ULD	Unlined	ext. dia. 14.5" x 11.25" H	DRM687-LD-11.3 lbs.DRM687-ULD-10 lbs.
DRM687-LD	Lined	ext. dia. 14.5" x 11.25" H	DRM687-LD-11.3 lbs.DRM687-ULD-10 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM687-ULD	Unlined	ext. dia. 36.8cm x 28.6cm H	DRM687-LD-5.1 kgDRM687-ULD-4.5 kg
DRM687-LD	Lined	ext. dia. 36.8cm x 28.6cm H	DRM687-LD-5.1 kgDRM687-ULD-4.5 kg

Specifications

Drum Lid Closure	Tight-Head
Lining	Lined; Unlined
Size	5 gal.
Thickness	0.9/0.9/0.9 mm Thick
Color	Black/White
Dimensions	ext. dia. 14.5" x 11.25" H
Storage Capacity	5 gal.
Bung Type	2" NPT and .75" NPT (Tri-Sure) Bungs
Drum Type	Steel Drum
Interior Dimensions	14" Dia. x 10.75" H
Lid Type	Tight-Head

Sold as	1 each
Weight	DRM687-LD-11.3 lbs.
Weight	DRM687-ULD-10 lbs.
# per Pallet	1
Composition	Drum - Steel Bung Gasket - EPDM
UNSPSC	24112108
Pigalog® Page Number	<u>Page 313</u>

Metric Equivalent

Dimensions	ext. dia. 36.8cm x 28.6cm H
Storage Capacity	18.9 L
Weight	DRM687-LD-5.1 kg
Weight	DRM687-ULD-4.5 kg

Technical Information

Certifications, Approvals and Ratings

UN1A1/X1.6/250



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com