



## 55-Gallon Quick-Style Open-Head UN Rated Steel Drum

DRM837 55 gal., UN1A2/X430/S, 1.5/1.5/1.5 mm

Tough, UN Rated open top drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Quick-style lever lock rings make it easy to comply with closure regs; no tools required
- Open-head design and removable lid offer full, convenient access to inside of drum
- Shippable "as is" so there's no need to switch closure rings as with other leverlock ring assemblies
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 16-gauge steel lid, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life

Item#	Description	Dimensions	Weight
DRM837-ULD	Unlined	ext. dia. 23.5" x 33" H	60 lbs.
DRM837-LD	Lined	ext. dia. 23.5" x 33" H	60 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM837-ULD	Unlined	ext. dia. 59.7cm x 83.8cm H	27.2 kg
DRM837-LD	Lined	ext. dia. 59.7cm x 83.8cm H	27.2 kg

### Specifications

Lining	Lined; Unlined
Thickness	1.5/1.5/1.5 mm
Color	Black/White
Dimensions	ext. dia. 23.5" x 33" H
Storage Capacity	55 gal.
Bung Type	No Bung Holes
Drum Type	Steel Drum
Lid Type	Open-Head - Quick-Style Lever Lock Band
Sold as	1 each
Weight	60 lbs.
# per Pallet	8

## Composition

Drum - 16-Gauge Steel  
Lever Ring - Galvanized Steel  
Lining - Phenolic Epoxy  
Gasket - EPDM

## UNSPSC

24112108

## Pigalog® Page Number

Page 308

## Metric Equivalent

### Dimensions

ext. dia. 59.7cm x 83.8cm H

### Storage Capacity

208.2 L

### Weight

27.2 kg

## Technical Information

### Certifications, Approvals and Ratings

UN1A2/X430/S



**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)