

Abocrete Structural Patching and Resurfacing Cement

PTY323 45 sq. ft. at 0.125" Deep Coverage Area, For Concrete

All-in-one epoxy kit makes concrete surfaces like new and ultra-hard.

- Provides up to 30 times the tensile strength and 21 times the flexural strength of concrete
- Mixes in minutes, sets in 20-40 minutes and dries in under 3 hours
- Apply in any thickness from a few mils to over 1 foot thick for jobs ranging from small repairs to major reconstruction
- All components are packaged inside one 5-gallon pail for convenient storage, carrying and mixing
- Resists oils, salts and other chemicals that corrode concrete
- Ideal for repair, patching or resurfacing floors, stairs, sidewalks, driveways, walls and columns
- Can also anchor items such as machines, signs, frames, furniture and bollards



Item#	Description	Dimensions	Weight
PTY323-LGY	Light Gray,		62 lbs.
PTY323-DGY	Dark Gray,		62 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
PTY323-LGY	Light Gray,		28.1 kg
PTY323-DGY	Dark Gray,		28.1 kg

Specifications

Use With	Concrete
Cure Time	3 Hours
Handling Time	20 to 40 Minutes
Temperature Limit	50°F (10°C) to 90°F (32°C)
Sold as	1 each
Weight	62 lbs.
# per Pallet	PTY323-LGY-36
Composition	Binder - Modified Epoxy Resin
	Activator - Amine
	Filler - Sand
Coverage Area	45 sq. ft. at 0.125" Deep

Includes

- 1 - 2 qt. Can Epoxy Resin
- 1 - 1 pt. Can Hardener
- 1 - Loose filler Sand aggregate filler
- 1 - 9" Pair of Gloves
- 1 - 8 oz. Plastic Bottle w/ Spout
- 1 - Paint Mixing Stick
- 1 - Putty Knife

Shelf Life

2 years

UNSPSC

13111001

Pigalog® Page Number

Page 275

Metric Equivalent

Weight

28.1 kg

Technical Information

CountryShipOnly

This product can ONLY be shipped to the United States or Guam.

Technical Documents

[Abocrete Structural Patching & Resurfacing Cement Part A](#)

[Abocrete Structural Patching & Resurfacing Cement Part B](#)

[Abocrete Structural Patching & Resurfacing Cement Part C](#)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com