

B-SAFE® Ball Valve Lockout

LCK120 Ball Valve Lockout, For 1.25" to 2.5" Valves w/ Handles from 7.5" to 10" L, 1 each

Ball valve LOTO installs in seconds to cover handle and prevent unauthorized use.

- Installs in seconds to completely cover handles and prevent unauthorized use
- Highly-visible, fully-dielectric polypropylene resists chemicals, cracking, abrasion, rust and extreme temperatures
- Accepts handles up to 1" wide
- Fits 1-1/4" to 2-1/2" valves with handles from 7-1/2" to 10" long and locks only in closed position
- Helps you meet 29 CFR 1910.147 regarding lockout/tagout procedures
- This simple lockout/tagout solution will help your facility meet life-saving regulations



Specifications

Use With	1.25" to 2.5" Valves w/ Handles from 7.5" to 10" L
Color	Red
Lockout Style	Ball Valve Lockout
Temperature Limit	-50°F (-46°C) to 360°F (183°C)
Sold as	1 each
Weight	0.5 lbs.
# per Pallet	288
Composition	Polypropylene
UNSPSC	46171511
Pigalog® Page Number	Page 256

Metric Equivalent

Weight	227 g
--------	-------

Technical Information

Technical Documents

29 CFR 1910.147

