

Barrier Vented Corner

PLR103 For 2" High Build-A-Berm Barrier, 2 each

Build a permanent barrier around your machinery or storage areas with our crush-resistant spill berms.

- Barriers can be constructed into a semi-permanent, high-visibility barrier that's exactly the size and shape you need - indoors or out
- Pliable open-cell foam barrier springs back into shape after you walk or roll over it with light, wheeled equipment
- Durable, 18-oz. all-vinyl covering resists oils, coolants and most chemicals
- Cut to length with utility knife; for best installation results, secure to a smooth, sealed surface with sealant and join seams with vinyl cement
- Contain leaks and spills around your machinery without building expensive concrete curbs or cutting and installing angle iron
- High-visibility yellow color draws attention to barrier for increased safety
- Easy removal requires only a flat-bladed shovel
- Great for use around battery charging stations, machinery or any other leak-prone areas
- Vent allows built-up air pressure caused by heavy vehicles driving over connected heavy-duty sections to escape without damaging your barrier



Specifications

Use With	2" High Build-A-Berm Barrier
Color	Yellow
Dimensions	5.5" W x 7.25" L x 2" H
Temperature Limit	Works from -22°F to 160°F
Sold as	2 per box
Weight	1.32 lbs.
# per Pallet	320
Composition	Cover - 18 oz. Vinyl-Coated Fabric Core - Open-Cell Polyurethane Foam
UNSPSC	24101907

Metric Equivalent

Dimensions	14cm W x 18.4cm L x 5.1cm H
Weight	.6 kg

Technical Information

Technical Documents

PIG Build-A-Berm® Barrier

Instructions for Using PIG® Build-A-Berm® Barrier

White paper – Should I be Worried about SPCC? 8 Things you need to know.

40 CFR 112.7

40 CFR 122.26

40 CFR 264.175



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com