

Bradley® Portable Drench Hose & Eye Wash

PLS1617 Portable, Holds 10 gal., Flow Rate 0.4 gal./Minute Minimum

Take this portable eye wash unit anywhere to provide ANSI-compliant emergency flushing.

- Sturdy stainless steel tank withstands industrial work sites; built-in handles make it easy to carry
- Fill unit with potable water and add preservative to keep clean and clear (water-treatment additive sold separately)
- 8' hose extends reach and full-size spray head fully flushes body or equipment
- Twin, chrome-plated brass eye wash heads create gentle cleansing streams when activated by large, highly visible push handle
- Stay-open valve prevents accidental shut off prior to full irrigation
- 10-gallon pressurized tank ensures ANSI standard 15 minutes of 0.4 gpm flow through eye wash or 3 minutes of 3 gpm flow through drench hose
- Tire-filler valve allows convenient pressurizing with standard air compressor or pump
- Attached gauge and relief valve help you monitor and maintain a safe pressure level
- Dust caps protect eye wash and drench hose heads from contamination and automatically release with activation



Specifications

Capacity	10 gal.
Style	Portable
Color	Silver
Dimensions	ext. dia. 12.25" x 24.38" H
Dispensing Method	Pressurized
Fluid Storage Method	Tank
Sold as	1 each
Weight	30.087 lbs.
# per Pallet	12
Composition	Stainless Steel

Flow Rate	0.4 gal./Minute Minimum
UNSPSC	46181810
Pigalog® Page Number	<u>Page 221</u>

Metric Equivalent

Dimensions	ext. dia. 31.1cm x 61.9cm H
Weight	13.6 kg

Technical Information

Certifications, Approvals and Ratings

ANSI Z358.1

USOnly

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

ANSI Z358.1

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

29 CFR 1910.151(c)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com