



## Diamond Sof-Tred™ Anti-Fatigue Mat Custom 3' Roll

FLM273 Not for Chemical Contact, Not for Oil/Grease Contact, 3' x 0.5"

Diamond plate-embossed mat features urethane top to seal out moisture and optional molded-in yellow border for extra visibility.

- Closed-cell PVC sponge mat is .5" thick to relieve leg and back fatigue
- Durable, abrasion-resistant Dyna-Shield urethane top coating seals out moisture and extends mat life
- Diamond-embossed surface provides traction and enables easy cleanup
- Beveled edges help reduce tripping hazard
- Custom length lets your mat match your workplace with clean, factory-cut edges



Item#	Description	Dimensions	Weight
FLM273		3' W x 0.5" H	2.4 lbs.
FLM273-BWY-CLR	Black w/ Yellow Border,	3' W x 0.5" H	2.4 lbs.
FLM273-BK-CLR	Black,	3' W x 0.5" H	2.4 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM273		91.4cm W x 12.7mm H	1.1 kg
FLM273-BWY-CLR	Black w/ Yellow Border,	91.4cm W x 12.7mm H	1.1 kg
FLM273-BK-CLR	Black,	91.4cm W x 12.7mm H	1.1 kg

### Specifications

Static-Dissipative	No
Drainage Holes	Without Holes
Anti-Slip	Yes
Dimensions	3' W x 0.5" H
Chemical Contact	Not for Chemical Contact
Oil/Grease Contact	Not for Oil/Grease Contact
Maximum Order Length	60
Minimum Order Length	2
Beveled Edge	Yes

<b>Brand</b>	No Trax
<b>Grit Surface</b>	No
<b>Safe for Welding Areas</b>	No
<b>Sold as</b>	1 foot
<b>Weight</b>	2.4 lbs.
<b># per Pallet</b>	16
<b>Composition</b>	Top Coat - Urethane Cushion - Closed-Cell PVC Sponge
<b>Application</b>	Dry Applications
<b>UNSPSC</b>	52101510
<b>Pigalog® Page Number</b>	<a href="#">Page 240</a>

## Metric Equivalent

<b>Dimensions</b>	91.4cm W x 12.7mm H
<b>Weight</b>	1.1 kg

## Technical Information

### Technical Documents

[NoTrax® Floor Matting](#)

### Disclaimers

#### Nominal Anti-Fatigue Mat Dimensions

Mat sizes are approximate as rubber shrinks and expands in conjunction with temperature and time. Tolerable manufacturing size variance is 3-5%.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)