



Diamond Sof-Tred™ Anti-Fatigue Mat Roll

FLM273 Not for Chemical Contact, Not for Oil/Grease Contact, 3' x 0.5"

Diamond plate-embossed mat features urethane top to seal out moisture and optional molded-in yellow border for extra visibility.

- Closed-cell PVC sponge mat is .5" thick to relieve leg and back fatigue
- Durable, abrasion-resistant Dyna-Shield urethane top coating seals out moisture and extends mat life
- Diamond-embossed surface provides traction and enables easy cleanup
- Beveled edges help reduce tripping hazard
- Custom length lets your mat match your workplace with clean, factory-cut edges



Item#	Description	Dimensions	Weight
FLM273		3' W x 0.5" H	2.4 lbs.
FLM273-BWY-CLR	Black w/ Yellow Border,	3' W x 0.5" H	2.4 lbs.
FLM273-BK-CLR	Black,	3' W x 0.5" H	2.4 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM273		91.4cm W x 12.7mm H	1.1 kg
FLM273-BWY-CLR	Black w/ Yellow Border,	91.4cm W x 12.7mm H	1.1 kg
FLM273-BK-CLR	Black,	91.4cm W x 12.7mm H	1.1 kg

Specifications

Static-Dissipative	No
Drainage Holes	Without Holes
Dimensions	3' W x 0.5" H
Chemical Contact	Not for Chemical Contact
Oil/Grease Contact	Not for Oil/Grease Contact
Maximum Order Length	60
Minimum Order Length	2
Beveled Edge	Yes
Brand	No Trax

Grit Surface	No
Safe for Welding Areas	No
Sold as	1 foot
Weight	2.4 lbs.
# per Pallet	16
Composition	Top Coat - Urethane Cushion - Closed-Cell PVC Sponge
Application	Dry Applications
UNSPSC	52101510
Pigalog® Page Number	<u>Page 230</u>

Metric Equivalent

Dimensions	91.4cm W x 12.7mm H
Weight	1.1 kg

Technical Information

Technical Documents

NoTrax® Floor Matting



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com