

# Double Junction Waterproof pHTestr™ 30

PLS1552 1.5" x 6.5", 1 each

Replaceable electrodes deliver accurate pH readings, even in harsh conditions.

- Dip in any liquid for accurate readings down to  $\pm 0.01$ ; capable of off-the-chart measurements from -1.00 to +15.00
- Easy-to-read screen displays pH and temperature; adjusts for fluctuating temperatures from 32°F to 122°F to offer greater reliability and consistency
- Unique double-junction electrode withstands plating baths, wastewater, process streams and other harsh liquids
- Intuitive 3-button controls, including one-touch calibration and hold function to freeze readings for later reference
- IP67 rated for protection of electronic equipment enclosures; waterproof, dustproof and will even float



## Specifications

<b>Dimensions</b>	ext. dia. 1.5" x 6.5" L
<b>Battery Requirements</b>	(4) 1.5V Alkaline Batteries (Included)
<b>Sensitivity Limit</b>	$\pm 0.01$ pH Accuracy & a Range of -1.00 to +15.00 pH
<b>Spill Kit Accessory Type</b>	Testing Supplies
<b>Temperature Limit</b>	Works in 32°F to 122°F (0°C to 50°C)
<b>Sold as</b>	1 each
<b>Weight</b>	1 lb.
<b>Composition</b>	Plastic
<b>Includes</b>	1 - pH Tester 1 - Lanyard 1 - Case
<b>Shelf Life</b>	3 years
<b>UNSPSC</b>	41113301
<b>Pigalog® Page Number</b>	<u><a href="#">Page 135</a></u>

## Metric Equivalent

<b>Dimensions</b>	ext. dia. 3.8cm x 16.5cm L
<b>Weight</b>	.5 kg

## Technical Information

<b>USOnly</b>	
---------------	--

This product can ONLY be shipped to the United States.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)