

FAST-ROCK™ Concrete Floor Patch

PTY314 35 sq. ft. at .125" Deep Coverage Area,
For Concrete

Fast-setting patch is traffic-ready in two hours and allows any depth repair.

- Ideal for high-traffic areas where setting speed and durability are crucial
- Chemical- and abrasion-resistant epoxy withstands harsh industrial environments
- Recommended for indoor use, but may be used outdoors if all moisture is removed while epoxy completely sets
- Perform deep or shallow repairs
- Fast two-hour set time helps you avoid long service interruptions
- All components are packaged inside a 5-gallon pail for convenient storage, carrying and mixing



Specifications

Use With	Concrete
Color	Gray
Application Temperature	60°F (15°C) to 75°F (24°C)
Cure Time	2 Hours
Handling Time	15 Minutes
Temperature Limit	50°F (10°C) to 90°F (32°C)
Sold as	1 each
Weight	34 lbs.
# per Pallet	48
Composition	Binder - Modified Epoxy Resin Activator - Amine Filler - Sand
Coverage Area	35 sq. ft. at .125" Deep
Includes	1 - 2 qt. Can Epoxy Resin 1 - 1 pt. Can Hardener 1 - Loose filler Sand aggregate filler
Shelf Life	1 year
UNSPSC	13111001

Metric Equivalent

Weight	15.4 kg
---------------	---------

Technical Information

USOnly

This product can ONLY be shipped to the United States.

StateNoShip

This product is subject to restrictions and cannot be shipped to Alaska or Hawaii.

Technical Documents

Fast-Rock Concrete Floor Patch (Part A)

Fast-Rock Concrete Floor Patch (Part B)

Fast-Rock Concrete Floor Patch (Part C)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com