

FTI Light-Duty Drum Pump

DRM1082 For Mildly Corrosive Acids; Cleaners; Bases; Lab Chemicals, Max Flow Rate 17 gal./Minute, 110V/60 Hz

Batch dispense mild corrosives, cleaners and lab chemicals with this economical, dual speed drum pump.

- Light-weight, easy-to-handle pump is perfect for intermittent liquid transfers
- 1/3 HP electric motor with dual speed toggle switch provides better flow control
- Impact-resistant plastic pump housing and pump tube withstand rust, corrosion and chemicals
- Pump tube diameter fits full-size drums and smaller carboys
- Includes a flexible 5'-long PVC discharge hose
- CSA-approved construction



Specifications

Speed	Dual
Max Flow Rate	17 gal./Minute
Max Viscosity	300 CentiPoise
Use With	Fits Up to 55 gal. Drum & Container w/ 2" Bung
Color	Blue/White
Brand	Finish Thompson
Compatible With	Mildly Corrosive Acids; Cleaners; Bases; Lab Chemicals
Explosion Proof	No
Powered By	Electric
Use With Flammables	No
Sold as	1 each
Weight	8.44 lbs.
Composition	Polypropylene, FKM, PTFE, ETFE, 316 Stainless Steel
Includes	1 - 40" L x 1.25" Dia. Pump Tube (DRM1081) 1 - Electric Motor (DRM1080) 1 - 5' L x .75" int. dia. PVC Discharge Hose
Power Requirements	110V/60 Hz
UNSPSC	40151529
Pigalog® Page Number	Page 332

Metric Equivalent

Weight 3.8 kg

Technical Information

Certifications, Approvals and Ratings

CSA Approved

CountryShipOnly

This product can ONLY be shipped to: United States, Canada, Mariana Islands, Mexico.

Certifications, Approvals and Ratings

CSA Approved

CountryShipOnly

This product can ONLY be shipped to: United States, Canada, Mariana Islands, Mexico.

Technical Documents

FTI Pumps

Pump Selection Guide



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com