

## Guardian Wall-Mount Eye Wash

PLS1619 Wall-Mount; Plumbed, Flow Rate 1.6 gal./Minute

Mount this emergency eyewash station on walls in high-risk areas so workers can flush away contaminants to help prevent serious injuries.



- Wall-mountable eye wash provides easy access to onsite initial treatment (mounting bracket included)
- Chrome-plated brass valve with PTFE seals stays open until manually closed for complete decontamination
- Stainless steel bowl with two spray heads delivers a flood of water for rinsing eyes
- Large push flag makes it easy to activate water flow, even when vision is compromised
- Spray heads include flip-top dust covers plus internal flow control and filter to remove impurities
- Assembled, inspected and water-tested before shipment to ensure quality and reliable performance at your facility



Item#	Description	Dimensions	Weight
PLS1619-SS	Stainless Steel,		6.15 lbs.
PLS1619-OR	Orange,		6.15 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
PLS1619-SS	Stainless Steel,		2.8 kg
PLS1619-OR	Orange,		2.8 kg

### Specifications

Capacity	Unlimited
Style	Wall-Mount; Plumbed
Dispensing Method	Plumbed
Sold as	1 each
Weight	6.15 lbs.
# per Pallet	45
Composition	Valve - Chrome Plated Brass

Bowl - ABS Plastic  
Mounting - Cast Aluminum  
Spray Heads - Polypropylene

**Flow Rate** 1.6 gal./Minute

**UNSPSC** 46181810

## Metric Equivalent

**Weight** 2.8 kg

## Technical Information

### Certifications, Approvals and Ratings

ANSI Z358.1

### Technical Documents

Compliance Checklist ANSI / ISEA Z358.1-2014

29 CFR 1910.151(c)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)