

GutterGuard Curb Inlet Guard

FLT559 For Sediment; Debris, 9" x 8', Max Flow Rate 400 gal./Minute

Block sediment and other debris from curb inlets and storm drains.

- To install, just place in front of curb inlet, with no weights or hardware required
- Keeps silt and debris out of curb-style storm drains
- During heavy rain, overflow ports prevent ponding in front of drain
- Reusable design can be cleaned and stored for less waste, expense and maintenance than other drain protection methods
- Useful as a best management practice in stormwater pollution prevention plans
- Ideal for construction sites, municipal streets, parking lots, etc



Specifications

Max Flow Rate	400 gal./Minute
Use With	Curb Opening up to 6'
Color	Gray/Yellow
Dimensions	ext. dia. 9" x 8' L
Recycled Content	100% Post-Consumer Recycled Polypropylene Fibers
Substance Filtered	Sediment; Debris
Sold as	1 each
Weight	19 lbs.
# per Pallet	10
Composition	Filter Skin - Polyethylene (HDPE) Mesh Rolled Media - Synthetic Fiber
UNSPSC	47101514
UV Resistant	Yes
Pigalog® Page Number	Page 278

Metric Equivalent

Dimensions

ext. dia. 22.9cm x 2.4m L

Weight

8.6 kg

Technical Information

Technical Documents

40 CFR 122.26



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com