

Non-Skid Step Tread

FLM646 6" x 24", 50 each

Precut, epoxy-coated grit treads are easy to apply to stairs or ramps.



- Rounded corners give a professional look, make application easier and won't lift or flag like conventional squared corners
- Durable mineral grit compound creates a non-skid surface for safe footing throughout your facility
- Grit is sealed with 2-part epoxy resin for durability and to prevent shedding
- Resists oil, water and heavy foot traffic for long service life
- Adhesive features low initial tack for minutes of easy repositioning
- Tape removes without residue
- Just remove protective backing and apply



Item#	Description	Dimensions	Weight
FLM646-BK	Black,	6" W x 24" L	7.834 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM646-BK	Black,	15.2cm W x 61cm L	3.6 kg

Specifications

Thickness	.9mm
Dimensions	6" W x 24" L
Installation Method	Self-Adhesive
Sold as	50 per package
Weight	7.834 lbs.
Composition	Mineral Abrasive Compound
UNSPSC	30161908

Metric Equivalent

Dimensions 15.2cm W x 61cm L

Weight 3.6 kg

Technical Information

Certifications, Approvals and Ratings

NFSI Certified

Technical Documents

29 CFR 1910.24(f)

29 CFR 1910.26(a)(1)(v)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com