



Optimax I Boom

BOM118 For Moderate Current, 100' x 19", 12" Draft Dimensions

Contain oil spills and debris in rough waters with the 6,400 lb. breaking strength of durable non-absorbent floating Optimax I Booms.

- Round polystyrene flotation boom corrals liquids and debris while skirting hangs below to keep pollutants from creeping under
- Vinyl-coated, UV-resistant polyester withstands up to 12-month deployment; 6,400 lb. breaking strength
- Link multiple booms with aluminum universal slide connectors
- Nylon handles allow single-person handling and anchoring
- Conforms to OPA-90 specs for protected water and fast currents
- Ideal in streams, rivers, estuaries, near-shore ocean environments and other areas with moderately fast flow
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)

Specifications

Style	Non-Absorbent Boom
Color	Yellow
Dimensions	100' L x 19" H
Current Type	Moderate Current
Intended Use	On Water
Sold as	1 each
Weight	200 lbs.
Composition	Skin - PVC Flotation - Polystyrene Chain - Galvanized Steel
Application	Spill Response
Draft Dimensions	12"
Freeboard Dimensions	7"
UNSPSC	24101907
Pigalog® Page Number	Page 185

Metric Equivalent

Dimensions

30m L x 48.3cm H

Weight

90.7 kg

Technical Information**Certifications, Approvals and Ratings**

AASHTO M-228 Erosion Class A

Technical Documents

33 CFR 154.1040

33 CFR 154.545(a)

40 CFR 112.7

40 CFR 122.26

**New Pig**

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-03041-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com