

Optimax II Boom

BOM119 For Strong Current, 50' x 20", 12" Draft Dimensions

Non-absorbent floating booms quickly contain oil spills and debris on rough, fast-flowing waters.

- Floating spill containment boom corrals liquids and debris while its skirting blocks pollutants underneath
- Vinyl-coated, UV-resistant polyester withstands up to 12-month deployment
- 6,400 lb. breaking strength
- Link multiple units using aluminum universal slide connectors
- Nylon handles allow single-person handling and anchoring
- Conforms to OPA-90 specs for protected water and fast currents in streams, rivers, estuaries and near-shore ocean
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)



Specifications

Style	Non-Absorbent Boom
Color	Yellow
Dimensions	50' L x 20" H
Current Type	Strong Current
Intended Use	On Water
Sold as	1 each
Weight	110 lbs.
Composition	Skin - PVC Flotation - Polystyrene Chain - Galvanized Steel
Application	Spill Response
Draft Dimensions	12"
Freeboard Dimensions	8"
UNSPSC	24101907
Pigalog® Page Number	Page 185

Metric Equivalent

Dimensions	15m L x 50.8cm H
Weight	49.9 kg

Technical Information

Certifications, Approvals and Ratings

AASHTO M-228 Erosion Class A

Technical Documents

33 CFR 154.1040

33 CFR 154.545(a)

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com