

# Pebble Step Sof-Tred™ Anti-Fatigue Mat

FLM127 For Light Chemical Splash, For Light Oil/Grease Splash, 3' x 5' x 0.375"



Dyna-Shield coating guards against chemical splashes and moisture penetration.

- 3/8" thick PVC sponge base reduces leg stress and strain
- Protective Dyna-Shield coating provides longevity, surface durability and chemical resistance
- Rounded edges and a pebble-top surface prevent slips or trips
- High-visibility yellow ramp increases visibility
- Beveled edges help reduce tripping hazard



## Specifications

Static-Dissipative	No
Drainage Holes	Without Holes
Color	Black w/ Yellow Border
Dimensions	3' W x 5' L x 0.375" H
Chemical Contact	For Light Chemical Splash
Oil/Grease Contact	For Light Oil/Grease Splash
Beveled Edge	Yes
Brand	No Trax
Grit Surface	No
Safe for Welding Areas	No
Sold as	1 each
Weight	11 lbs.
# per Pallet	56
Composition	Dyna-Shield® PVC Sponge

<b>Application</b>	Dry Applications
<b>UNSPSC</b>	52101510
<b>Pigalog® Page Number</b>	<u>Page 231</u>

## Metric Equivalent

<b>Dimensions</b>	91.4cm W x 152.4cm L x 9.5mm H
<b>Weight</b>	5 kg

## Technical Information

### Technical Documents

NoTrax® Floor Matting



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)