

PIG® Above-the-Ceiling Leak Diverter

TLS620 Ceiling Tiles, Diverter Only, 22.25" x 32.25" x 7.25"



This lightweight leak diverter sits directly above your ceiling tile to channel liquid away and help prevent damage.

- Installed diverter remains completely out of view while diverting ceiling leaks
- Mounted on a light-weight, sturdy frame that sits on suspended 2' x 2' or 2' x 4' acoustical tile
- Nonpermeable tarp is vinyl-coated for strength and durability; resists punctures, UV and mildew for long life
- Captured liquid drains through a 1/4" port into the attached 25' long PVC hose
- Assembles in less than 5 minutes, then it's ready to install above your drop ceiling
- Install side by side to protect larger areas



Item#	Description	Dimensions	Weight
TLS620-CL	Clear,	22.25" W x 32.25" L x 7.25" H	5.375 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS620-CL	Clear,	56.5cm W x 81.9cm L x 18.4cm H	2.4 kg

Specifications

Style	Diverter Only
Dimensions	22.25" W x 32.25" L x 7.25" H
Drainage Hose Included	Yes
Hanging Straps Included	No
Hose Connector	.25"
Installation Method	Frame
Shape	Rectangle
Sold as	1 each
Weight	5.375 lbs.
New Pig Patent	7,331,357
# per Pallet	80

Composition	Diverter - PVC w/ Polyester Reinforcement Frame, Hose - PVC
Application	Ceiling Tiles
Flow Rate	1 gal./Minute
Includes	1 - Leak Diverter 1 - Frame 1 - 25' L Hose 4 - 6" L PVC Legs
UNSPSC	24141506
Pigalog® Page Number	<u>Page 264</u>

Metric Equivalent

Dimensions	56.5cm W x 81.9cm L x 18.4cm H
Weight	2.4 kg

Technical Information

Technical Documents

[Instructions for Installing PIG® Above the Ceiling Leak Diverter](#)

Disclaimers

[Assembly Required](#)

[Maximum Working Temperature](#)

Not suitable for temperatures over 170°F/77°C.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com