

PIG™ Conical Drain Plug Kit

PLR207 Fits 2" to 4" Dia. Drains

Seal drains below the grate without the hassle or permanence of cement.

- Durable polyurethane plug forms a liquid-tight, chemical-resistant seal in seconds
- Just wedge plug in drain for an easy alternative to permanently sealing your drains with cement
- Installed plug is low-profile enough to fit below floor grate
- Allows your drain to function normally when plug is not in place; removes easily with hand-tools
- Kit contains three sizes to seal drains from 2" to 4" in diameter
- Packed in a plastic case for easy storage



Specifications

Color	Yellow
Dimensions	4.75" W x 15" L x 7.75" H
Drain Size	2" to 4" Dia. Drains
Ideal For	Long-Term Use
Sold as	3 per box
Weight	6 lbs.
# per Pallet	160
Composition	Plug - Polyurethane Eye Bolt - Metal
Includes	1 - 2.25" X 5.25" Conical Drain Plug (PLR208) 1 - 3.35" X 5.25" Conical Drain Plug (PLR209) 1 - 4.25" X 5.5" Conical Drain Plug (PLR210)
UNSPSC	40141738
UV Resistant	No
Pigalog® Page Number	<u>Page 173</u>

Metric Equivalent

Dimensions

12.1cm W x 38.1cm L x 19.7cm H

Weight

2.7 kg

Technical Information**Technical Documents**

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[PIG® Blocker Family](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

Disclaimers**Urethane Notice**

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com