

## PIG® Envirosolv UN Rated Overpack Salvage Drum Plus

PAK229 95 gal., UN1H2/X295/S, .25" Thick

Our toughest overpack is over-engineered to be even stronger and tighter sealing for use in the harshest environments. 95-gallon overpack is designed for leaking drums up to 55 gallons.

- X-rated for Packing Groups I, II and III, so it's ideal for regulated packaging applications, including shipping hazardous waste by land, sea or rail
- Specifically sized and designed for leaking drums up to 55 gallons
- X-base design makes opening and closing overpack easy for one person
- Drum base accepts a 2x4 or pole so you can stabilize bottom of drum while you tighten the leak-proof lid
- Male/female pattern on lid and base lock together stacked overpacks for secure storage
- Extra-long side shoulders and sturdy rib design provide added strength and stability
- Overpack can be moved easily with a forklift
- Polyethylene material with UV inhibitors is durable, light-weight and chemical-resistant
- Crush-resistant gasket with memory creates a tight, non-slip seal to keep drum contents secure
- Designed and proven to withstand shipping abuse



### Specifications

Drum Lid Closure	Open-Head
Lining	Unlined
Size	95 gal.
Thickness	.25" Thick
Color	White
Dimensions	ext. dia. 32" x 44" H
Storage Capacity	95 gal.
Bung Type	No Bung Holes
Drum Type	Poly Drum

<b>Interior Dimensions</b>	25" Dia. x 37" H
<b>Lid Type</b>	Screw-Top
<b>Sold as</b>	1 each
<b>Weight</b>	56 lbs.
<b># per Pallet</b>	2
<b>Composition</b>	Polyethylene
<b>UNSPSC</b>	24112109
<b>Pigalog® Page Number</b>	<a href="#">Page 319</a>

## Metric Equivalent

<b>Dimensions</b>	ext. dia. 81.3cm x 111.8cm H
<b>Storage Capacity</b>	359.6 L
<b>Weight</b>	25.4 kg

## Technical Information

### Certifications, Approvals and Ratings

UN1H2/X295/S

### Technical Documents

LDPE Products

49 CFR 173.3(c)(1)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)