

PIG® Grippy® Adhesive-Backed Absorbent Mat

MAT3251 Mediumweight, 32" x 40", 1 roll

Make the switch to the mat that sticks! Absorbent runner catches drips from vehicles or industrial equipment, and it won't blow away when the door is open.



- Adhesive-backed absorbent mat stays exactly where you put it with no shifting or bunching up underfoot
- Fits perfectly underneath vehicles to protect shop floors from oily leaks and drips; reduces cleanup time to keep your shop productive
- Sticks to most commercial floor surfaces including concrete, VCT, linoleum, ceramic tile, quarry tile and laminate flooring
- Proprietary adhesive sticks to the floor with a super-tight grip, but can be easily removed and repositioned so you can reuse the mat until it becomes saturated
- Tough, spunbond top layer with heavy-duty zigzag stitching stands up to rolling tires and service bay foot traffic
- Eight layers of fine-fiber polypropylene safely absorb and retains oils, coolants, water, grease, gasoline, solvents, auto fluids, paint overspray, battery acid and most other liquids
- Leakproof backing prevents absorbed liquid from soaking through to the floor
- Dark color hides grime so the mat looks cleaner longer
- Mat ends are heat-cut for a finished, professional look
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Grippy Absorbent Mat have been proven to reduce slip-and-fall claims by as much as 90%
- Mats take on the properties of absorbed liquids
 - always take proper precautions when handling saturated absorbents



Specifications

Antimicrobial	No
Traffic	Medium Foot Traffic
Backing Material	Adhesive-Backed
Indoor/Outdoor	Indoor Use
Incinerable	Yes
Flammability Specifications	Flame Resistant - Will melt and self-extinguish
Fluid Absorbed	Oils, Coolants, Solvents, Water – Universal
Color	Blue
Dimensions	32" W x 40" L
Mat Weight	Mediumweight
Recycled Content	25% or more Recycled Content
Absorbency	Up to .35 gal. per roll
Brand	PIG
Category	Grippy® Absorbent Mat
Core Diameter	3"
Industry	Industrial Facilities; Shops & Garages
Perforated	No
Storage Temp Range	Store between 32°F and 120°F
Temperature Limit	Surface temps from 55°F to 120°F
Walking Surface	Absorbent Top
Sold as	1 roll
Weight	1.8 lbs.
New Pig Patent	Patent Pending
# per Pallet	500
Composition	Absorbent - Polypropylene Stitching - Polyester Adhesive Backing - Proprietary Adhesive Material
UNSPSC	47131901
UV Resistant	No
Pigalog® Page Number	Page 19

Metric Equivalent

Absorbency	Up to 1.3 L per roll
Dimensions	81.3cm W x 101.6cm L
Weight	.8 kg

Technical Information

Certifications, Approvals and Ratings

NFSI Certified,ANSI B101.1- 2009,Meets NFPA 99 Static Decay and Resistivity Requirements

Technical Documents

[PIG Grippy® Absorbent Mat](#)

[Static Coefficient Of Friction \(SCOF\) Testing](#)

[How to use PIG Grippy Absorbent Mat](#)

[White paper – Slip & Fall Prevention Secrets](#)

[PIG Adhesive-Backed Mats ADA Compliance](#)

[PIG® Grippy® Absorbent Mats](#)

[29 CFR 1910.22\(a\)\(2\)](#)

Disclaimers

[Safety Instructions Regarding Flammable Liquids for Flame Resistant Mats](#)

Pig Absorbent Mats are flame resistant in their unused state, but take on the properties of flammable liquids they absorb. Always take proper precautions against potential ignition in handling and disposal of these mats if they have absorbed flammable liquids. For further assistance, please call Technical Services.

[Color Variation Statement](#)

It is normal for top layer materials to show minor variations in color between production runs. This is particularly true for the grades of materials used in consumable or disposable products such as our adhesive-backed mats. New Pig makes every effort to achieve consistent color, but some variance is possible. Perceived differences in color may also result from mat layout orientation or uneven traffic wear patterns.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com