

PIG® Leak Diverter for Spraying Pipes

TLS147 Pipes, Diverter Only, 28.5" x 16"

Purpose-built design catches pipe leaks or condensation to protect equipment, inventory and personnel.

- Material wraps completely around 3/4" to 4" diameter pipes to capture and contain sprays, drips and accumulated condensation
- Nonpermeable tarp is vinyl-coated for strength and durability; resists punctures, UV and mildew for long life
- Tapered design helps funnel liquid toward center for better drainage
- Hook-and-loop fasteners make installation quick and easy and secures diverter in place
- Accepts a standard 3/4" hose connection to channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 3.33 gallons per minute when used with a 1/2" ID hose
- Need a custom size or solution? Just call 1-800-HOT-HOGS (468-4647)



Item#	Description	Dimensions	Weight
TLS147-YW	Yellow,	28.5" W x 16" H	0.661 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS147-YW	Yellow,	72.4cm W x 40.6cm H	.3 kg

Specifications

Style	Diverter Only
Dimensions	28.5" W x 16" H
Drainage Hose Included	No
Hanging Straps Included	No
Hose Connector	.75"
Installation Method	Velcro
Shape	Rectangle
Sold as	1 each

Weight	0.661 lbs.
Composition	PVC, Polyester
Application	Pipes
Flow Rate	3.33 gal./Minute
UNSPSC	24141506
Pigalog® Page Number	<u>Page 263</u>

Metric Equivalent

Dimensions	72.4cm W x 40.6cm H
Weight	.3 kg

Technical Information

Technical Documents

[Instructions for Assembling PIG® Leak Diverter System](#)

[Instructions for Installing PIG® Leak Diverter for Horizontal Pipes](#)

Disclaimers

[Maximum Working Temperature](#)

Not suitable for temperatures over 170°F/77°C.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com