

## PIG® Oil-Only Absorbent Boom

BOM304 8" x 10', Absorbs up to 12 gal. per boom, 4 booms

Confine and absorb oil and fuel spills on land or water.

- Field-proven performance works in all conditions to absorb oil spills on land or water
- Floats to confine and soak up spills on water; hugs ground for land-based spills
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 400-lb. loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant up to 12 months; meets NFPA 99 standards for static decay
- Booms float at surface for easy retrieval, even when saturated
- Absorbs and retains oils and oil-based liquids - including lubricants and fuels - without taking in a drop of water
- Strong, zinc-plated carbon steel attachment clips and rings allow you to link booms together for greater length
- Bright white color makes booms easier to see in outdoor environments and clearly shows saturation level
- Can be incinerated after use to reduce waste or for fuels blending



### Specifications

<b>Fluid Absorbed</b>	Oils, Fuels, Other Oil-Based Liquids Only
<b>Color</b>	White
<b>Dimensions</b>	ext. dia. 8" x 10' L
<b>Recycled Content</b>	98% Pre-Consumer Recycled Polypropylene Filler
<b>Absorbency</b>	Up to 48 gal. per bag
<b>Absorbency per</b>	Up to 12 gal. per boom
<b>Clip/Ring</b>	Zinc Plated Carbon Steel
<b>Filler</b>	Polypropylene

<b>Skin/Outer Mesh</b>	Skin - Polypropylene, Outer Mesh - Polyester
<b>Sold as</b>	4 booms per bag
<b>Weight</b>	45.5 lbs.
<b>NSN (National Stock Number)</b>	7930-01-436-8326
<b># per Pallet</b>	8
<b>Application</b>	Spill Response
<b>UNSPSC</b>	47131907
<b>Pigalog® Page Number</b>	<u>Page 65</u>

## Metric Equivalent

<b>Absorbency per</b>	Up to 45.4 L per boom
<b>Absorbency</b>	Up to 181.7 L per bag
<b>Dimensions</b>	ext. dia. 20.3cm x 3m L
<b>Weight</b>	20.6 kg

## Technical Information

### Certifications, Approvals and Ratings

NFPA 99

### Technical Documents

[UV-Resistance Comparison Testing of Spunbond and Meltblown](#)

[Instructions for Using PIG® Absorbent Booms](#)

[PIG® Oil-Only Absorbents](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)