

## PIG® Pipe Leak Diverter

TLS691 Pipes, Diverter System, 24" x 24"

Purpose-built design catches pipe leaks or condensation to protect equipment, inventory and personnel.

- Hangs from a leaking pipe to catch nuisance leaks and channel them to a floor drain or collection container
- Nonpermeable tarp is vinyl-coated for strength and durability; resists punctures, UV and mildew for long life
- Built-in brass grommets and included 14"-long rubber straps make it easy to hang from an overhead pipe
- Choose yellow for high visibility, gray to blend with plant ceilings or clear to monitor leaks
- Flow rate of 3.33 gallons per minute when used with a 1/2" ID hose



| Item#     | Description | Dimensions            | Weight     |
|-----------|-------------|-----------------------|------------|
| TLS691-YW | Yellow,     | ext. dia. 24" x 24" H | 2.433 lbs. |
| TLS691-GY | Gray,       | ext. dia. 24" x 24" H | 2.433 lbs. |
| TLS691-CL | Clear,      | ext. dia. 24" x 24" H | 2.433 lbs. |

### Metric Equivalent:

| Item#     | Description | Dimensions              | Weight |
|-----------|-------------|-------------------------|--------|
| TLS691-YW | Yellow,     | ext. dia. 61cm x 61cm H | 1.1 kg |
| TLS691-GY | Gray,       | ext. dia. 61cm x 61cm H | 1.1 kg |
| TLS691-CL | Clear,      | ext. dia. 61cm x 61cm H | 1.1 kg |

### Specifications

|                         |                       |
|-------------------------|-----------------------|
| Style                   | Diverter System       |
| Dimensions              | ext. dia. 24" x 24" H |
| Drainage Hose Included  | No                    |
| Hanging Straps Included | Yes                   |
| Hose Connector          | .75"                  |
| Installation Method     | Hanging Straps        |
| Shape                   | Circle                |
| Sold as                 | 1 each                |

|                             |   |
|-----------------------------|---|
| <b>Weight</b>               | 2.433 lbs.  |
| <b># per Pallet</b>         | 96  |
| <b>Composition</b>          | Diverter (Colors) - PVC, Polyester<br>Leak Diverter (Clear) - PVC w/ Polyester Reinforcement<br>Straps - Rubber |
| <b>Application</b>          | Pipes   |
| <b>Flow Rate</b>            | 3.33 gal./Minute  |
| <b>Includes</b>             | 1 - Leak Diverter<br>1 - Hose Connector<br>4 - Rubber Hanging Straps  |
| <b>UNSPSC</b>               | 24141506  |
| <b>Pigalog® Page Number</b> | <u><a href="#">Page 267</a></u>   |

## Metric Equivalent

|                   |                         |
|-------------------|-------------------------|
| <b>Dimensions</b> | ext. dia. 61cm x 61cm H |
| <b>Weight</b>     | 1.1 kg                  |

## Technical Information

### Technical Documents

[Instructions for Assembling PIG® Leak Diverter System](#)

### Disclaimers

#### Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)