

PIG® Poly Spill Pallet with Hinged Hardcover



PAK608 Holds (4) 55 gal. Steel Drums, 57.25" x 54" x 60", 66 gal. Sump Capacity

Open the "gull wing" doors and load your drums inside this economical hard cover pallet. Great for outdoor drum storage on a budget.

- Economical "gull wing" hardcovers allow easy access while providing protected storage and liquid containment
- Support hinges lock in place to keep cover up and out of the way while you load or unload
- Weather-resistant design prevents contaminants from entering storm water
- Low-density polyethylene (LDPE) construction with UV inhibitors resists UV rays, rust, corrosion and most chemicals
- Optional .75" drain plug lets you empty sump without removing drums or grating
- Padlockable; attaches at hinge



Item#	Description	Dimensions	Weight
PAK608-WOD	Without Drain	57.25" W x 54" D x 60" H	226 lbs.
PAK608-WD	With Drain	57.25" W x 54" D x 60" H	226 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
PAK608-WOD	Without Drain	145.4cm W x 137.2cm D x 152.4cm H	102.5 kg
PAK608-WD	With Drain	145.4cm W x 137.2cm D x 152.4cm H	102.5 kg

Specifications

Headroom	6.75"
Holds	(4) 55 gal. Steel Drums
Color	Black/White
Dimensions	57.25" W x 54" D x 60" H
Load Capacity UDL	3000 lbs.
Sump Capacity	66 gal.
Access	2 Hinged Doors

Drain	Optional .75" Drain
Fork Truck Access	Four-Way Fork Truck Access
Interior Dimensions	48" W x 48" D x 42" H
Use With Flammables	No
Sold as	1 each
Weight	226 lbs.
# per Pallet	1
Composition	Pallet - Polyethylene (LDPE) w/ UV Inhibitors Grates - Injection-Molded Polyethylene
UNSPSC	24101905
Pigalog® Page Number	Page 380

Metric Equivalent

Dimensions	145.4cm W x 137.2cm D x 152.4cm H
Load Capacity UDL	1360.8 kg
Sump Capacity	249.8 L
Weight	102.5 kg

Technical Information

Technical Documents

LDPE Products

[40 CFR 112.7](#)

[40 CFR 122.26](#)

[40 CFR 264.175](#)

Disclaimers

Flammables Notice

If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources. For further assistance, please call Technical Services.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com