

PIG® Roof Leak Diverter Bucket Kit

TLS121 Roofs, All Inclusive Kit, 5' x 5'

Our portable Leak Diverter Bucket Kits are perfect for grab-and-go response to overhead leaks.

- Contains supplies for rapid response to roof leaks, all in a 6.5-gallon pail
- Pail lid has a removable plug to allow the drainage hose to be inserted without having to remove the lid
- Pail can be used as a collection container for diverted liquid; printed "Caution" message doubles as a warning sign
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Flow rate of 3.33 gallons per minute when used with a 1/2" ID hose
- Translucent material lets light through and allows easy monitoring of leak
- 60"-long adjustable straps allow fast setup and response
- Need a custom size or solution? Just call 1-800-HOT-HOGS (468-4647)



Item#	Description	Dimensions	Weight
TLS121-TR	Translucent,	5' W x 5' L	11 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS121-TR	Translucent,	152.4cm W x 152.4cm L	5 kg

Specifications

Style	All Inclusive Kit
Dimensions	5' W x 5' L
Drainage Hose Included	Yes
Hanging Straps Included	Yes
Hose Connector	.75"
Installation Method	Hanging Straps

Shape	Square
Sold as	1 each
Weight	11 lbs.
# per Pallet	27
Composition	Diverter - PVC, Polyester Hose - PVC Straps - Nylon Bucket - Plastic
Application	Roofs
Flow Rate	3.33 gal./Minute
Includes	1 - 5' L x 5' W Leak Diverter 1 - 25' L Clear Drainage Hose (TLS679) 4 - 60" L Adjustable Hanging Straps (TLS559) 1 - 6.5-gal. Bucket
UNSPSC	24141506
Pigalog® Page Number	<u>Page 260</u>

Metric Equivalent

Dimensions	152.4cm W x 152.4cm L
Weight	5 kg

Technical Information

Technical Documents

[Instructions for Assembling PIG® Leak Diverter System](#)

Disclaimers

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.

Nominal Leak Diverter Dimensions

Dimensions are nominal size due to pinched corners and reinforced side walls.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com