

PIG® Roof Leak Diverter

TLS462 Roofs, Diverter System, 5' x 5'

Stop devastating roof leak damage and protect your people, equipment and inventory with the original diverter. Invented here!



- The original Leak Diverter - invented here and engineered to stop devastating roof leak damage every time, guaranteed
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Ideal for quick response to avoid downtime after a roof leak or for long-term prevention in leak-prone areas
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- Pinched corners help funnel liquid toward center for better drainage
- Accepts a standard 3/4" hose connection to channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 3.33 gallons per minute when used with a 1/2" ID hose
- Brass grommets and stainless-steel D-rings resist tearing and make installation easy



Item#	Description	Dimensions	Weight
TLS462-TR	Translucent,	5' W x 5' L	2.693 lbs.
TLS462-GY	Gray,	5' W x 5' L	2.693 lbs.
TLS462-CL	Clear,	5' W x 5' L	2.693 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS462-TR	Translucent,	152.4cm W x 152.4cm L	1.2 kg
TLS462-GY	Gray,	152.4cm W x 152.4cm L	1.2 kg
TLS462-CL	Clear,	152.4cm W x 152.4cm L	1.2 kg

Specifications

Style	Diverter System
Dimensions	5' W x 5' L

Drainage Hose Included	No
Hanging Straps Included	No
Hose Connector	.75"
Installation Method	Hanging Straps
Shape	Square
Sold as	1 each
Weight	2.693 lbs.
# per Pallet	480
Composition	Diverter (Colors) - PVC, Polyester Leak Diverter (Clear) - PVC w/ Polyester Reinforcement
Application	Roofs
Flow Rate	3.33 gal./Minute
Includes	1 - Leak Diverter 1 - Hose Connector
UNSPSC	24141506
Pigalog® Page Number	<u>Page 263</u>

Metric Equivalent

Dimensions	152.4cm W x 152.4cm L
Weight	1.2 kg

Technical Information

Technical Documents

[White paper – Slip & Fall Prevention Secrets](#)

[Instructions for PIG Leak Diverter Systems](#)

Disclaimers

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.

Nominal Leak Diverter Dimensions

Dimensions are nominal size due to pinched corners and reinforced side walls.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com