


## PIG® SpillBlocker® Tabletop Dike

PLR229 Ideal For Worksurface Spill Response, Labs, One 1" W x 4' L x 0.75" H Section

Contain small spills on workbenches or in labs with this liquid-proof, low-profile mini-barrier.

- Contains benchtop spills without absorbing; ideal for small spills on smooth work surfaces
- Polyurethane material resists water, oils and many chemicals
- High-visibility yellow color draws attention to spill for increased safety
- Reusable dike cleans easily with soap and water
- Comes in compact storage box for easy transport
- Cut to any length for a custom fit
- Can also be used to form an edge on workbenches to keep bolts, bearings and other small parts from rolling off



### Specifications

Traffic	Non-Weight Bearing
Barrier Dimensions	One 1" W x 4' L x 0.75" H Section
Color	Yellow
Dimensions	1" W x 4' L x 0.75" H
Ideal For	Worksurface Spill Response, Labs
Install/Deploy Type	Temporary/Removable Barrier
Intended Use	Table Top
Max liquid temp exposure	Max Exposure Limit 225°F for up to 30 Minutes
Temperature Limit	Works from 0°F to 160°F
Sold as	1 per box
Weight	2 lbs.
New Pig Patent	5,236,281
# per Pallet	750
Composition	Polyurethane
UNSPSC	24101907

Pigalog® Page Number

Page 164

Metric Equivalent

**Dimensions**

2.5cm W x 121.9cm L x 1.9cm H

**Weight**

.9 kg

**Technical Information****Technical Documents**[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)[Urethane Use, Care and Storage](#)[PIG Spillblocker Dike Instructions](#)[PIG® Blocker Family](#)[40 CFR 112.7](#)[40 CFR 122.26](#)**Disclaimers****Urethane Notice**

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.

**One Pork Avenue • Tipton, PA 16684-0304**1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)