

PIG® Spring-Open Roof Leak Diverter Kit

TLS752 Roofs, All Inclusive Kit, 30"

Go from storage bag to fully functioning leak diverter in less than two minutes!

- Coiled diverter springs open for hassle-free installation in under two minutes
- Rigid outer rim holds diverter open for easy handling
- 60"-long straps, hooks and clamps can be adjusted in seconds; just nudge your diverter until it's centered and leveled, even if hanging points are uneven
- All diverter components are preattached for speedy setup; flexible PVC drainage hose (included) clicks into place with preinstalled quick-connect adapter
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Brass grommets resist tearing and make installation easy
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- Conical shape helps funnel liquid toward center for better drainage; translucent color helps monitor debris and liquid flow
- Flow rate of 3.33 gallons per minute when used with supplied 1/2" ID hose
- Ready to use right out of the convenient storage bag



Item#	Description	Dimensions	Weight
TLS752-CL	Clear,	ext. dia. 30"	4.885 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS752-CL	Clear,	ext. dia. 76.2cm	2.2 kg

Specifications

Style	All Inclusive Kit
Dimensions	ext. dia. 30"

Drainage Hose Included	Yes
Hanging Straps Included	Yes
Hose Connector	.75" w/ Quick Connect
Installation Method	Hanging Straps
Shape	Circle
Sold as	1 each
Weight	4.885 lbs.
New Pig Patent	Patent Pending
# per Pallet	102
Composition	Diverter - PVC, Polyester Hose - PVC Hooks - Plastic
Application	Roofs
Flow Rate	3.33 gal./Minute
Includes	1 - 30" Dia. Leak Diverter 1 - Quick Connect (TLS645) 1 - 25' L Clear Drainage Hose (TLS679) 2 - 60" L Adjustable Hanging Straps 4 - Hanging Hooks 1 - Vinyl Storage Bag
UNSPSC	24141506
Pigalog® Page Number	Page 266

Metric Equivalent

Dimensions	ext. dia. 76.2cm
Weight	2.2 kg

Technical Information

Technical Documents

[Spring-Open Leak Diverter FAQ](#)

[Instructions for Spring-Open Leak Diverter](#)

Disclaimers

[Maximum Working Temperature](#)

Not suitable for temperatures over 170°F/77°C.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com

