

PIG™ Steel Epoxy Putty

PTY264 6 - 4 oz. Tubes

Special PIG Epoxy Putty formulations cover nearly any application. Guaranteed to work or your money back.



- Specially formulated with the highest-quality epoxy resins to bond and blend with ferrous metals
- Convenient, premeasured epoxy has Parts A and B in the same tube
- Mixes easily simply by kneading to a uniform color
- Cures concrete-hard in 1 hour; once cured, putty can be drilled, sawed, filed, tapped, machined, sanded or painted
- Nontoxic, VOC- and solvent-free putty can be used on potable water lines
- 3- to 5-minute working time
- Can be used indoors or out
- A great addition to any toolbox or response kit
- PIG Putty is not intended for making structural repairs



Specifications

Color	Gray
Dimensions	7" L
Handling Time	3 Minutes
Pipe Size	Unlimited
Pipe Pressure	Pressurized, Non-Pressurized
Repair Type	Permanent
Temperature Limit	-40°F (-40°C) to 250°F (121°C) Continuous, 300°F (149°C) Intermittent
Sold as	6 per box
Weight	2 lbs.
Composition	15% Epoxy Resins 1.5% Catalyst 83.5% Non-Hazardous Proprietary Ingredient
Application	Steel
Shelf Life	2 years
UNSPSC	31201607

Volume	4 oz. Tube
Pigalog® Page Number	Page 272

Metric Equivalent

Dimensions	17.8cm L
Weight	.9 kg

Technical Information

Certifications, Approvals and Ratings

NSF Certified

CountryNoShip

This product is subject to export restrictions and cannot be shipped to Canada.

Certifications, Approvals and Ratings

NSF Certified

CountryNoShip

This product is subject to export restrictions and cannot be shipped to Canada.

Technical Documents

[PIG® Repair Putty](#)

[Instructions for PIG Steel Epoxy Putty](#)

[PIG® Steel Repair Putty](#)

Disclaimers

[For Repair Purposes Only](#)

Not intended for structural applications. For repairing applications only.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com