

PIG® Trough Style Roof Leak Diverter

TLS561 Roofs, Diverter Only, 16" x 15'

Stop devastating roof leak damage and protect your people, equipment and inventory with the original diverter. Invented here!



- The original Leak Diverter - invented here and engineered to stop devastating roof leak damage every time, guaranteed
- Long, rectangular shape is ideal for catching leaks or accumulated condensation along cracks, fissures or pipes
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Ideal for quick response to avoid downtime after a roof leak or for long-term prevention in leak-prone areas
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- Pinched corners help funnel liquid toward center for better drainage
- Grommets resist tearing and make installation easy
- 16" width fits easily between joists
- Accepts a standard 3/4" hose connection to channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 3.33 gallons per minute when used with a 1/2" ID hose
- Edges feature rods along length for additional stability
- Rods split at 5' lengths for easy storage
- Need a custom size or solution? Just call 1-800-HOT-HOGS (468-4647)



Item#	Description	Dimensions	Weight
TLS561-TR	Translucent,	16" W x 15' L	9 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS561-TR	Translucent,	40.6cm W x 4.6m L	4.1 kg

Specifications

Style	Diverter Only
Dimensions	16" W x 15' L
Drainage Hose Included	No
Hanging Straps Included	No
Hose Connector	.75"
Installation Method	Hanging Straps
Shape	Rectangle
Sold as	1 each
Weight	9 lbs.
# per Pallet	60
Composition	Diverter - Vinyl-Coated Nylon
Application	Roofs
Flow Rate	3.33 gal./Minute
UNSPSC	24141506
Pigalog® Page Number	Page 259

Metric Equivalent

Dimensions	40.6cm W x 4.6m L
Weight	4.1 kg

Technical Information

Technical Documents

[Instructions for Assembling PIG® Leak Diverter System](#)

[Instructions for Installing Large PIG® Leak Diverter for Roofs](#)

[White paper – Slip & Fall Prevention Secrets](#)

Disclaimers

[Maximum Working Temperature](#)

Not suitable for temperatures over 170°F/77°C.

[Nominal Leak Diverter Dimensions](#)

Dimensions are nominal size due to pinched corners and reinforced side walls.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com

