

PipeSock

FLT564 For Oil; Sediment, For Up to 8" Dia. Pipes, Max Flow Rate 106 gal./Minute

Pipe sock fits 8" dia. pipes to help you control and contain oil and sediment during dewatering and pump-outs of sumps and collection ponds.

- Simply attach to hose or pipe to remove hydrocarbons and sediment from pumped water
- X-Tex recycled fibers provide high efficiency and excellent flow
- Incinerable and fuels-blendable with high Btu value and low ash
- Attaches easily to pipes and hoses with a simple pipe clamp or heavy zip tie (not included)
- Ideal for pumping out containment areas, collection ponds, utility vaults and sumps



Specifications

Max Flow Rate	106 gal./Minute
Capacity	1.7 cu. ft.
Style	Oil, Water, Sediment Separators
Thickness	115.5 mil Thick
Use With	Up to 8" Dia. Pipes
Color	Black
Dimensions	ext. dia. 8" x 5' L
Recycled Content	100% Post-Consumer Recycled Synthetic Fibers
Absorbency	Up to .81 gal.
Micron Rating	150 Microns
Separator Type	Dewatering & Silt Bags & Socks
Substance Filtered	Oil; Sediment
Sold as	1 each
Weight	2 lbs.

# per Pallet	140
Composition	X-TeX™ Fibers
Includes	1 - Pipe Sock 1 - 60" H x 36" W Disposal Bag
UNSPSC	47101525
Pigalog® Page Number	<u>Page 279</u>

Metric Equivalent

Absorbency	Up to 3.1 L
Dimensions	ext. dia. 20.3cm x 152.4cm L
Weight	.9 kg

Technical Information

Technical Documents

Why is there no SDS?

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com