

Straight-Sided Open-Head UN Rated Poly Drum

DRM1059 55 gal., UN1H2/X200/S, UN1H2/Y250/S, .135" Thick

Straight sidewall allows broader use of drum grabs and other equipment that can't latch on to tapered drums.

- Straight sidewalls allow broader use of drum grabs, parrot beak lifters and other equipment that can't move tapered drums
- Ribs add strength and rigidity; UN Rated for storage and transport of solid hazardous materials
- High-density polyethylene won't rust or corrode
- Quick-release lever lock band can be wire sealed to deter unauthorized access
- Compatible with a wide range of liquids and chemicals



Specifications

Drum Lid Closure	Open-Head
Lining	Unlined
Size	55 gal.
Thickness	.135" Thick
Color	Blue
Dimensions	ext. dia. 23" x 37" H
Storage Capacity	55 gal.
Bung Type	No Bung Holes
Drum Type	Poly Drum
Interior Dimensions	22.5" Dia. x 36" H
Lid Type	Screw-Top
Temperature Limit	160°F (71°C) Maximum Temperature
Sold as	1 each
Weight	23 lbs.
# per Pallet	3
Composition	Polyethylene (HDPE)
UNSPSC	24112109

Pigalog® Page Number

Page 315

Metric Equivalent

Dimensions	ext. dia. 58.4cm x 94cm H
Storage Capacity	208.2 L
Weight	10.4 kg

Technical Information

Certifications, Approvals and Ratings

UN1H2/X200/S,UN1H2/Y250/S



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com