

Zee Line Air-Operated Double Diaphragm Transfer Pump System

DRM1287 For Motor Oil; Waste Oil; ATF, Max Flow Rate 14 gal./Minute

Move waste oil quickly and easily with this aluminum-base transfer pump and system components.

- Flow rate is up to 14 gallons per minute (GPM)
- Aluminum base with polypropylene center section pump; 3/4" NPT inlet and outlet pumps, Buna-N diaphragm, acetal balls and aluminum seats
- For use with waste oil, gear lube and automatic transmission fluid (ATF)
- Non-stalling and lube-free
- System includes male and female cam locks, brass ball valves, hydraulic adapter swivel, street elbow, suction hose, discharge hose, nipple, strainer, airline filter and reducer bushing
- Mounting bracket lets you install pump on a wall, table or cart near your transfer station
- Pump has bolt pattern of 3.25" x 4.37" and stands 10.25"H



Specifications

Speed	Single
Max Flow Rate	14 gal./Minute
Max Viscosity	140 wt.
Use With	Waste Oil Pump System
Color	Black/Red/White
Brand	Zeeline
Compatible With	Motor Oil; Waste Oil; ATF
Explosion Proof	No
Powered By	Air
Use With Flammables	No
Sold as	1 each
Weight	32 lbs.
Composition	Body- Aluminum and Polypropylene Diaphragm- Buna N Balls- Acetal Seats Aluminum Valves- Brass Elbow-

Galvanized Nipples- Galvanized

Includes

1 - Double Diaphragm Pump (DRM1284)
1 - 3/4" Male Camlock
1 - 3/4" Female Camlock
3 - 3/4" Brass Ball Valve
2 - 1/2" x 3/4" Hydraulic Adapter Swivel
1 - 3/4" Galvanized Steel Street L
1 - 3/4" x 8' Suction Hose
1 - 3/4" x 8' Discharge Hose
2 - 3/4" x 2" Nipple
1 - 3/4" Strainer
1 - Wall Mount Bracket
1 - Airline Filter

Power Requirements

100 PSI @ 16 CFM

UNSPSC

40151529

Pigalog® Page Number

[Page 334](#)

Metric Equivalent

Weight

14.5 kg

Technical Information

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

[Pump Selection Guide](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com