

Zee Line Air-Operated Oil Drum Pump with Nozzle

DRM164 For Oil-Based Liquids; Lubricants, Max Flow Rate 5 gal./Minute, 50-145 PSI

Easily dispense oils and lubricants from tight-head drums using compressed air. Great for farm and fleet!

- Dispenses motor oils, gear oils, automatic transmission fluids and other petroleum-based lubricants
- Attaches to 30- and 55-gallon tight-head drums with 2" NPT bung
- 3:1 ratio, low-pressure pump is specifically designed for pumping liquids through a hose reel
- Z-Swivel and 25' medium-pressure dispensing hose aides lubrication for hard-to-reach machinery
- Durable hose has maximum working pressure of 4,500 pounds
- Oil control handle keeps output regulated and consistent
- Delivery rate of up to 5 gallons per minute
- Low-pressure steel pump has a 2" bung adapter and 22.5" extension tube
- Air regulator combination unit includes an air line filter with automatic water drain, a regulator gauge and ball valve
- Ideal for use in industrial, automotive, agricultural and construction applications



Specifications

Speed	Single
Max Flow Rate	5 gal./Minute
Max Viscosity	90 wt.
Use With	Fits 30 & 55 gal. Drum w/ 2" NPT Bung
Color	Black/Blue/Silver
Air Line Input Fitting	.25" Air Line Fitting
Brand	Zeeline
Compatible With	Oil-Based Liquids; Lubricants
Explosion Proof	No

Powered By	Air
Use With Flammables	No
Sold as	1 each
Weight	21.78 lbs.
Composition	Pump - Steel Hose - Rubber w/ Metal Fittings Handle - Plastic w/ Metal Fittings
Includes	1 - Air Operated Pump (DRM696) 1 - 25'L Dispensing Hose (DRM162) 1 - Oil Control Handle (DRM163)
Power Requirements	50-145 PSI
UNSPSC	40151529
Pigalog® Page Number	Page 333

Metric Equivalent

Weight	9.9 kg
---------------	--------

Technical Information

Technical Documents

[Pump Selection Guide](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com