

## Zee Line Stainless Steel Rotary Hand Drum Pump - PTFE Seals

DRM988 For Corrosives; Fuels, Max Flow Rate 6 oz./Revolution, Max Viscosity 60 wt.

Quickly pump corrosive chemicals, fuels and other flammables from your drums with this versatile stainless steel rotary hand-operated pump.

- Stainless steel construction is compatible with corrosive chemicals and fuels
- Rotary design with aluminum handle provides single-motion dispensing
- PTFE vanes, stainless steel spring and PTFE seals are chemical-resistant
- PTFE tape (included) provides an excellent seal between pickup tube sections
- Moves up to 6 oz. of fluid per revolution
- Use with up to SAE 50 wt. viscosity or 880 cP
- Rubber water deflector keeps moisture from entering drum through bung adapter
- Pump can be grounded for use with fuels and chemicals
- Hose barb adapter secures a 3/4" hose (not included) onto spout for dispensing at a distance
- Safety locking pin secures handle to prevent accidental discharge
- Fits 15-, 30- or 55-gallon drums with 2" NPT bungs
- 3-piece stainless steel pickup tube and bung adapter let you adjust height



### Specifications

Max Flow Rate	6 oz./Revolution
Max Viscosity	60 wt.
Use With	15 to 55 gal. Drum w/ 2" NPT Bung
Color	Silver
Brand	Zeeline
Compatible With	Corrosives; Fuels
Manual Pump Type	Rotary Operated
Powered By	Manual
Use With Flammables	Yes

<b>Sold as</b>	1 each
<b>Weight</b>	13.611 lbs.
<b># per Pallet</b>	180
<b>Composition</b>	Body - 304 Stainless Steel Vanes, Shaft Seal - PTFE
<b>Includes</b>	1 - Roll of Teflon tape for joints 1 - Pump
<b>UNSPSC</b>	40151529
<b>Pigalog® Page Number</b>	<u>Page 323</u>

## Metric Equivalent

<b>Weight</b>	6.2 kg
---------------	--------

## Technical Information

### Technical Documents

[Zee Line Pump](#)

[Pump Selection Guide](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)